

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	
OFFICE	

NEW MEXICO OIL CONSERVATION COMMISSION RECEIVED

MAR 30 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-61

5a. Location Type of	<input checked="" type="checkbox"/> On
5b. Well No.	
7. Unit Agreement	
8. Name of Operator	Jackson "AT"
9. Well No.	8
10. Name of Well	Eagle Creek (S.A.)
11. Elevation (Show whether DF, RT, GR, etc.)	Eddy

SUNDY NOTICES AND REPORTS ON WELLS **ARTESIA, OFFICE**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

☒ ALL ☐ GAS WELL ☐ OTHER

1. Name of Operator
Yates Petroleum Corporation

2. Address of Operator
207 South 4th Street - Artesia, NM 88210

3. Location of Well
UNIT LETTER J 2310 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 14 TOWNSHIP 17S RANGE 25E

4. Elevation (Show whether DF, RT, GR, etc.)
3487' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT ON:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEILING <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent data, etc.)

work) SEE RULE 1103.

Spudded a 15" hole at 1:30 PM 3-16-76.

TD 397'. Ran 10 joints of 10-3/4" 40# used casing (402.93') set at 397' KB. Cemented by Denton w/225 sacks of Class "C" w/4% CaCl. PD 3:30 AM 3-17-76. Cement did not circulate. Filled hole w/Ready Mix after WOC 4 hours. WOC 12 hours, nipples up and cut off casing, drilled plug, reduced hole to 9 1/2" and resumed drilling.

TD 1193'. Ran 29 joints of 7" 20# K-55 ST&C (1193.41') of casing set at 1193' KB. Centralizers at 1175' and 605', cement baskets at 647 and 566'. Cemented by Denton w/350 sacks of Lite + 2% CaCl, followed w/150 sacks of Class "C" 2% CaCl. PD 6:15 PM 3-18-76. Cement did not circulate. WOC 6 hours and ran Temperature Survey, found top of cmt at 740'. Ran 1" to 683', spotted 50 sacks of Class "C" 4% CaCl. PD 1:45 AM 3-19-76. Ran 1" to 570' & spotted 50 sacks of Class "C" 4% CaCl. PD 4:30 AM 3-19-76. Ran 1" to 570'. Spotted 50 sacks of Class "C" 4% CaCl. PD 7:00 AM 3-19-76. Dumped 10 cubic feet of pea gravel at 8:30 AM 3-19-76. Ran 1" at 444' and spotted 50 sacks of Class "C" 4% CaCl, in place at 9:00 AM 3-19-76. Ran 1" to 413', spotted 50 sacks of Class "C" 4% CaCl, in place at 11:00

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

(Attached -Continued)

SIGNED Christina Amelin TITLE Geol. Secty DATE 3-29-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAR 30 1976

CONDITIONS OF APPROVAL, IF ANY:

Yates Petroleum Corporation
Jackson "AT" No. 8
14-17S-25E, Eddy Co., NM

7" casing continued:

3-19-76. Pulled up 1" to 245', spotted 80 sacks of Class "C" 4% CaCl₂ in place at 11:30 AM 3-19-76. Cement circulated. WOC 18 hours, cut off 7" casing, nipples up, installed BOP's and tested to 1000#. OK. Drilled plug and tested to 600#. OK. Reduced hole to 6 $\frac{1}{4}$ " and resumed drilling.