

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR - 7 1976

Form 1-101
Supersedes 111
6-100 and 6-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEAT PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM 1-100) FOR SUCH PROPOSALS.)

ARTESIA OFFICE

1. ☐ OIL ☒ GAS WELL ☐ OTHER	2. Unit Agreement
3. Name of Operator Yates Petroleum Corporation	4. Well Name Gable "FV" Com
5. Address of Operator 207 South 4th Street - Artesia, NM 88210	6. Well No. 1
7. Location of Well UNIT LETTER <u>H</u> <u>660</u> FEET FROM THE <u>East</u> LINE AND <u>1980</u> FEET FROM THE <u>North</u> LINE, SECTION <u>29</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM	8. Undesignated
9. Elevation (Show whether DF, RT, GP, etc.) 3588' GP	10. Body

16. Check Appropriate Box To Indicate Nature of Notice, Action, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent work) SEE RULE 1103.

Spudded a 17½" hole at 9:45 AM 3-24-76. Ran 7 joints of 13-3/8" 48# H-40 (205.64') of casing set at 202' KB. Cmt'd by Denton w/200 sacks of Class "C" 4% CaCl. PD 8:30 PM 3-24-76. Cmt circ. WOC 12 hrs, cut off csg, 10' and drilled plug. Reduced hole to 12¼" and resumed drilling.
TD 1100' - Ran 27 jts of 8-5/8" 24# K-55 ST&C (1122.58') of csg set at 1100' KB, 1-Tex Pattern Shoe, centralizers at 1059 and 540', baskets at 582 & 499'. Cmt'd by Denton w/350 sx of Lite 2% CaCl followed w/150 sx of Class C 2% CaCl. PD 12:45 PM 3-29-76. Did not circ. Ran Temp Survey, top of cmt at 730' at 7:15 PM 3-29-76. Ran 1" to 567', sptd 100 sx of Class C 4% CaCl. Pld 1" & WOC 3 hrs. Ran 1" and tagged top of cmt at 283', sptd 50 sx of Class C 4% CaCl at 273' in place at 3:00 AM 3-30-76. Pld. 1" and WOC 3 hrs, ran 1" and tagged cmt at 283', sptd 50 sx of Class C 4% CaCl at 273'. PD 6:15 AM 3-30-76. Pld 1" & WOC 3 hrs, tagged cmt at 252', sptd 75 sx of Class C 4% CaCl in place at 9:30 AM 3-30-76. WOC 3 hrs & tagged cmt at 185'. Sptd 75 sx of Class C 4% CaCl, filled to surface. Cmt circulated. In place at 2:00 PM 3-30-76. WOC 18 hours, cut off casing, nipples up, tested BOP's to 1000#. OK. Drilled plug and tstd to 600#. OK. Reduced hole to 7-7/8" & resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge.

SIGNED Christine Tomlinson

TITLE Geol. Secty

4-6-76

APPROVED BY W. A. Gessert

TITLE SUPERVISOR, DISTRICT II

DATE APR - 9 1976

CONDITIONS OF APPROVAL, IF ANY: