

13 8 1/2 7'
5' x 8 1/2"

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Jenkins Bros. Drilling Co.</u>		Lease <u>Boling State</u>		Well # <u>2</u>	
Location of Well	Unit # <u>16503 8900</u>	Section <u>9</u>	Township <u>17</u>	Range <u>28</u>	County <u>Eddy</u>
Drilling Contractor	<u>CC Tools</u>		Type of Equipment <u>Cable</u>		

* Continued

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>10</u>	<u>8"</u>	<u>26</u>		<u>150</u>	
<u>8"</u>	<u>7"</u>	<u>24</u>		<u>450</u>	
* <u>6"</u>	<u>4 1/2"</u>	<u>9</u>		<u>700</u>	<u>2nd Casing</u>

Casing Data:

Prod 22 joints of 4 1/2 inch 9.5 # Grade J-55

(Approved) (~~Rejected~~)

Inspected by Nick Tanker date 7-16-76

Cementing Program

Size of hole 6" Size of Casing 4 1/2 Sacks cement required 175

Type of Shoe used Halliburton Float collar used Halliburton Btm 3 jts welded No

TD of hole 701' Set 70.5 Feet of 4 1/2 Inch 9.5 # Grade J-55

New-used csg. @ 70.5 with 175 sacks neat cement around shoe

+ 175 sax Class C additives 50 Right Poz

Plug down @ 5.00 (~~PM~~) (PM) Date 7-16-76

Cement circulated Yes No. of Sacks 10

Cemented by Dowell Witnessed by Nick Tanker

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: