

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND	FILE
OPER	OR

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 24 1976
O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Terry "FU"
9. Well No. 1
10. Field or Pool, or Wildcat Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well Oil <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER F , 1980' FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 16S RANGE 25E NMPM.
15. Elevation (Show whether DF, RT, GP, etc.) 3515' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING Casing <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated cost of work) SEE RULE 1103. any proposed

Spudded a 17½" hole at 10:30 PM 5-14-76.

TD 324' - Ran 7 joints of 13-3/8" 48# H-40 casing set at 324'. Cemented w/250 sacks of Class "C" 4% CaCl. Cement circulated. PD 8:00 AM 5-15-76. WOC 12 hours, cut off casing, nipples up, reduced hole to 12½", drilled plug and resumed drilling.

TD 1020' - Ran 25 joints of 8-5/8" 24# K-55 (1023') of new casing set at 1020'. Cemented w/350 sacks of Halli-Lite, 5# gilsonite and 1/4# flocele 2% CaCl followed w/100 sacks of Class "C" 2% CaCl. PD 4:00 AM 5-17-76. Cement circulated. WOC 18 hours, nipples up, installed BOP's pressured up to 1000#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Tomlinson</u>	TITLE <u>Geol. Secty</u>	DATE <u>5-21-76</u>
APPROVED BY <u>W. A. Gussess</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAY 24 1976</u>

CONDITIONS OF APPROVAL, IF ANY: