

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA F.	
FILE	1
U.S.G.S.	
LAND FICE	
OPER OR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

SUNDY NOTICES AND REPORTS ON WELLS MAY 27 1976

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Yates Petroleum Corporation	3. Address of Operator 207 South 4th Street-Artesia, NM 88210	4. Location of Well UNIT LETTER F 1650 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 17S RANGE 25E NMPM.	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	5. State Oil & Gas Lease No.
6. Name of Operator Yates Petroleum Corporation	7. Unit Agreement Name	8. Farm or Lease Name Jackson Estate "BY"	9. Well No. 7	10. Field Pool, or Wildcat Eagle Creek S.A.	
11. Elevation (Show whether DF, RT, GR, etc.) 3537' GR	12. County Eddy				

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒

ALTERING OPERATIONS ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated completion date) SEE RULE 1103.

Spudded a 15" hole at 8 PM 5-18-76.

TD 308' - Ran 9 joints of 10-3/4" 40# used casing (310.9') set at 308' KB. Cemented by Denton w/225 sacks of Class "C" 4% CaCl. PD 9:00 AM 5-19-76. Cement circulated. WOC 12 hours, cut off casing, nipples up, reduced hole to 9 1/2", drilled plug and resumed drilling.

TD 1170' - Ran 29 joints of 7" 20# K-55 ST&C R3 (1173.26') set at 1170' KB, notched joint on bottom, centralizers at 1128 and 675', baskets at 716 and 634'. Cemented by Denton w/350 sacks of Lite 2% CaCl followed w/150 sacks of Class "C" 2% CaCl. PD at 10:20 AM 5-21-76. Cement circulated. WOC 3 hours and cement and cement dropped, filled hole to surface w/Ready-Mix. WOC 18 hours, cut off casing, nipples up and tested BOP's to 1000# OK. Reduced hole to 6 1/4", drilled plug and tested cement to 600#. OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty

5-27-76

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II

DATE MAY 28 1976

CONDITIONS OF APPROVAL, IF ANY: