

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND	FICE
OPER	OR

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
JUN 9 1976

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Form of Lease Name Jackson Estate "BY"
9. Well No. 8
10. Field Name Eagle Creek S.A.
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
 Yates Petroleum Corporation ✓

3. Address of Operator
 207 South 4th Street - Artesia, NM 88210

4. Location of Well
 UNIT LETTER L 430 FEET FROM THE West LINE AND 2310 FEET FROM
 THE South LINE, SECTION 22 TOWNSHIP 17S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GP, etc.)
 3545' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

Spudded a 15" hole at 10:30 PM 5-27-76.
 TD 250' - Ran 6 joints of 10-3/4" 40# used casing (236.41') set at 250' KB.
 Cemented w/150 sacks of Class "C" 4% CaCl. PD 8:30 AM 5-28-76. Cement circulated. WOC 12 hours, cut off casing, nipples up, reduced hole to 9 1/2" and resumed drilling after drilling out plug.
 TD 1148' KB. Ran 27 joints of 7" 20# K-55 casing (1150.08') set at 1148' KB. 1-Guide shoe, centralizers at 1132, 627' and baskets at 668 and 582'. Cemented by Denton w/350 sacks of Lite followed by 150 sacks of Class "C" 2% CaCl. PD 4:30 AM 5-30-76. Cement did not circulate. WOC and Ran Temperature Survey. Ran 1" to 273' and spotted 50 sacks of Class "C" 4% CaCl. PD 11:30 AM 5-30-76. ~~Used 50 sacks of Ready Mix, 2% cacl and had returns to surface.~~ Mixed 50 sacks of Class "C" 4% CaCl, followed w/2 1/2 yards of Ready Mix. Cement circulated. WOC 18 hours, cut off casing, nipples up and installed BOP's tested to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600# OK, and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 6-8-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 10 1976

CONDITIONS OF APPROVAL, IF ANY: