

NO. OF COPIES RECEIVED			
DISTRIBUTION			
SANTA FE			
FILE			
U.S.G.S.			
LAND	FICE		
OPER	OR		

RECEIVED
 NEW MEXICO OIL CONSERVATION COMMISSION
JUN 16 1976

Form C-103
 Supersedes Old
 C-102 and C-101
 Effective 1-1-61

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Well
State <input type="checkbox"/> Fed <input checked="" type="checkbox"/>
5. Name of Oil & Gas Company
7. Unit Agreement Name
8. Former Lease Name
McCaw "BT"
9. Well No.
3
10. Field Name of Well
Eagle Creek S.A.
12. County
Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator	Yates Petroleum Corporation
3. Address of Operator	207 South 4th Street - Artesia, NM 88210
4. Location of Well	UNIT LETTER <u>A</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.
15. Elevation (Show whether DF, RT, GP, etc.)	3488' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG & ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated completion date, if proposed)

Spudded a 15" hole at 1:00 PM 6-1-76.
 Ran 10 joints of 10-3/4" 40# used casing (351.51') set at 350' KB.
 Cemented by Denton w/200 sacks of Class "C" 4% CaCl. PD 12:30 AM 6-2-76. Cement circulated. WOC 12 hours. Cut off landing joint, nipples up, reduced hole to 9 1/2", drilled plug and resumed drilling. TD 1200'. Ran 29 joints of 7" 20# K-55 ST&C casing (1223.98') set at 1200' KB. 1-Howco Guide Shoe on bottom. No centralizers or baskets. Cemented w/350 sacks of Lite plus 150 sacks of Class "C" 2% CaCl. PD 7:45 AM 6-5-76. Cement did not circulate. WOC 6 hours and ran Temperature Survey and found top of cement at 930'. Ran 1" at 420' and spotted 50 sacks of Class "C" 4% CaCl. PD 3:00 PM 6-5-76. WOC. Ran 1" to 399' and spotted 200 sacks of Class "C" w/30% Strata-Crete plus 4% CaCl. PD 6:30 PM 6-5-76. WOC ran 1" to 389' and spotted 75 sacks of Class "C" 4% CaCl at 9:50 PM 6-5-76. Cement circulated. Cut off casing, nipples up, tested BOP's to 1000#. OK. Reduced hole to 6 1/4", drilled out and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Imhusen TITLE Geol. Secty DATE 6-14-76

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: