

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA I	1
FILE	1
U.S.G.S.	
LAND	FICE
OPER	OR

RECEIVED NEW MEXICO OIL CONSERVATION COMMISSION

JUN 21 1976

O. C. C.
ARTESIA, OFFICE

Form C-101
Supersedes C-101
C-102 and C-103
Effective 1-1-76

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN EXISTING WELLS IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO REOPEN EXISTING WELLS IN A DIFFERENT RESERVOIR.

1. ☒ **WELL** ☐ **GAS WELL** ☐ **OTHER**

2. Name of Operator

Yates Petroleum Corporation

McCaw "BT"

3. Address of Operator

207 South 4th Street - Artesia, NM 88210

3

4. Location of Well

UNIT LETTER A 990 FEET FROM THE North LINE AND 330 FEET FROM THE

Eagle Creek S.A.

THE East LINE, SECTION 14 TOWNSHIP 17S RANGE 25E

15. Elevation (Show whether DF, RT, GP, etc.)
3488' GR

Eddy

16. Check Appropriate Box To Indicate Nature of Notice Report or Order To
NOTICE OF INTENTION TO: SUBSEQUENT REPORT ON:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☒
CASING TEST AND CEMENT ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, times, and weather conditions.) SEE RULE 1103.

Spudded a 15" hole at 1:00 PM 6-1-76.

Ran 10 joints of 10-3/4" 40# used casing (351.51') set at 350' KB. Cemented by Denton w/200 sacks of Class "C" 4% CaCl. PD 12:30 AM 6-2-76. Cement Circ. WOC 12 hours. Cut off landing joint, nipples up, reduced hole to 9 1/2", drilled plug and resumed drilling.

TD 1200' - Ran 29 joints of 7" 20# K-55 ST&C casing (1223.98') set at 1200' KB. 1-Howco Guide Shoe on bottom. No centralizers or baskets. Cemented w/350 sacks of Lite plus 150 sacks of Class "C" 2% CaCl. PD 7:45 AM 6-5-76. Cement did not circulate. WOC 6 hours and ran Temperature Survey and found top of cement at 930'. Ran 1" at 420' and spotted 50 sacks of Class "C" 4% CaCl. PD 3:00 PM 6-5-76. WOC. Ran 1" to 399' and spotted 200 sacks of Class "C" w/30% Strata-Crete plus 4% CaCl. PD 6:30 PM 6-5-76. WOC ran 1" to 389' and spotted 75 sacks of Class "C" 4% CaCl at 9:50 PM 6-5-76. Cement circulated. WOC 18 hours, cut off casing, nipples up, tested BOP's to 1000# OK. Reduced hole to 6 1/4", drilled out and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Geol. Secty

6-17-76

APPROVED BY Charles J. Johnson
CONDITIONS OF APPROVAL, IF ANY:
For Record Only

TITLE _____ DATE JUN 21 1976