

DEPARTMENT OF THE INTERIOR

(Other instructions on reverse side)

Budget Bureau No. 42-R1424

GEOLOGICAL SURVEY

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Yates Petroleum Corporation ✓		8. FARM OR LEASE NAME Federal "GC" Com	
3. ADDRESS OF OPERATOR 207 South 4th Street-Artesia, NM 88210		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FEL of Section 32-17S-25E		10. FIELD AND POOL, OR WILDCAT Eagle Creek Permo Penn	
14. PERMIT NO.		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 32-17S-25E Unit P NMPM	
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 3604' KB		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☒

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Permo Penn Completion

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The Richard Knob-Atoka Morrow and Eagle Creek Strawn completions were temporarily abandoned by setting a standing valve in the On-off tool on Guiberson packer at 7805'. Set Retrievable bridge plug at 6617'. Perforated and treated the Eagle Creek Permo Penn. perforations thru straddle packers as follows:

6583-6600' - 34 0.32" holes, treated w/1300 gallons of 15% DS-30 acid.

6524-6528' - 8 0.32" holes, treated 6524-6600' w/2700 gallons 15% DS-30 acid

6276-6280' - 8 0.32" holes, treated w/1000 gallons 15% DS-30 acid.

After recovering load, well flowed 55 psig on 1/4" choke = 95 MCFPD.

(9-20-78).

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 9-28-78

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE SEP 29 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side