

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | 2 |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

AUG 13 1976

O. C. C.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator Marbob Energy Corporation | 8. Farm or Lease Name N G Phillips State |
| 3. Address of Operator P. O. Box 304, Artesia, N. M. 88210 | 9. Well No. 20 |
| 4. Location of Well UNIT LETTER P 965.2 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 17 S RANGE 28 E NMPM. | 10. Field and Pool, or Wildcat East Empire Yates S R |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3665.5 G L | 12. County Eddy |

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
running 8 5/8" casing to shut off water ☒
Running 7" casing to shut off water ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 6-15-76

6-18-76 ran 245' 8 5/8" casing to shut off water
6-29-76 Ran 500' 7" surface casing to shut off water
7-27-76 Attempted to pull 8 5/8" casing, pipe stuck, backed off, pulled 90 ft., left 155 ft 8 5/8" casing in hole, Pulled 500' 7" before running 4 1/2"
7/27/76 Ran 906 ft new 4 1/2" 10.5# casing, Halliburton cemented with 100 sx lite and 75 sx 50/50 pozmix C, cement circulated, cement fell back to 107', filled to surface with 4 yards ready mix.
Total depth 910 ft.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dorothy Hammond TITLE Agent DATE 8/12/76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 13 1976

CONDITIONS OF APPROVAL, IF ANY: