

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other Instructions
on reverse side)Form approved
Budget Bureau No. 42-R1424

5. LEASE DENOMINATION AND SERIAL NO.

NM 0219603

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

AUG 12 1976

O.C.C.
ARTESIA, OFFICE1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

330' FNL & 2310' FEL of Section 28-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3563' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "BZ"

9. WELL NO.

14

10. FIELD AND POOL, OR WILDCAT

Eagle Creek S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 28-17S-25E
Unit B NM PM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-30-76 - TD 249'. Spudded a 15" hole at 10:00 AM 7-30-76. Drilled to 249' and ran 7 joints of 10-3/4" 40# used casing (250.10') set at 294' KB. Cemented by Denton w/150 sacks of Class "C" 4% CaCl. PD 8:00 PM 7-30-76. WOC 12 hours cut off casing, reduced hole to 9-7/8", drilled plug and resumed drilling.

TD 1136'. Ran 27 joints of 7" 20# K-55 used casing (1141.29') set at 1136' KB. 1-Texas shoe, centralizers at 1093 and 630'. Baskets at 669-586'. Cemented by Denton w/350 sacks of mix 2% CaCl followed w/150 sacks of Class "C" 2% CaCl. PD 7:25 PM 8-1-76. Cement circulated. WOC 18 hours, nipples up, tested BOP's to 1000#. OK. Drilled plug, tested to 600#. OK, reduced hole to 6 1/4" and resumed drilling.

RECEIVED

AUG 11 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine L. Linder

TITLE

Geol. Secty

DATE

8-10-76

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side