

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Yates Petr Corp.</i>		Lease <i>McLaw BT</i>		Well # <i>4</i>	
Location of Well	Unit # <i>1650N 990E</i>	Section <i>14</i>	Township <i>17</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Byrd & Co.</i>			Type of Equipment <i>Rotary to start 7-20-76</i>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>15"</i>	<i>10 3/4"</i>	<i>32</i>		<i>300</i>	<i>Circulate</i>
* <i>9 1/2"</i>	<i>7"</i>	<i>20</i>		<i>1180</i>	<i>"</i>
<i>6 1/4"</i>	<i>4 1/2 + 5 1/2"</i>	<i>10.5 + 15.5</i>		<i>1500</i>	<i>"</i>

Casing Data:

Int.
Surface *28* joints of *7* inch *20* # Grade *K-55*

(Approved) (~~Rejected~~)

Inspected by *Nick Tinker* date *7-22-76*

Cementing Program

Size of hole *9 1/2* Size of Casing *7* Sacks cement required *350 5x*

Type of Shoe used *Tx Shox* Float collar used *No* Btm 3 jts welded *Thread Locked*

TD of hole *1197 DF* Set *1184* Feet of *7* Inch *20* # Grade *K-55*

New-used csg. @ *1184* with *350* sacks *510* cement around shoe *150 5x class C*
+ *sax* additives *5/10% GILS. 1% LIGHT 1/4" ROSEAL. 2% CC IN POT*

Plug down @ *11:45* (AM) (~~PM~~) Date *7-22-76*

Cement circulated _____ No. of Sacks _____

Cemented by _____ Witnessed by _____

* Temp. Survey ran @ *6:30 (AM)* (PM) Date *7-22-76* top cement @ *5' 25'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

* Remarks: *Cemented up 1" log from 350' to surface approx 10 5x to put*