

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Marbob Energy Corp		Lease N.B. Phillips ST		Well # 21	
Location of Well	Unit	Section 27	Township 17	Range 28	County Eddy
Drilling Contractor Durries			Type of Equipment CT		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12"	10 3/4"	-		565	Pull
9"	7 5/8"	26.40		898'	circ

Casing Data:

Surface 30 joints of 7 5/8 inch 26.40# Grade Used K-55 API
(Approved) (Rejected)

Inspected by Selan Mermis date 9-1-76

Cementing Program 565' of 12", 333' of 9"

Size of hole 12", 9" Size of Casing 7 5/8 Sacks cement required 325

Type of Shoe used Texas Pm Float collar used Insert Btm 2 jts welded Thread Lock

TD of hole 898' 6L Set 892' 6L Feet of 7 5/8 Inch 26.40# Grade K-55

New-used csg. @ 892' 6L with 100 sacks neat cement around shoe Class C 50-80 Pz
+ 225 sax Howco lite additives 1/4" floccul 50 sand 8 salt

Plug down @ 5:20 (AM) (PM) Date 9-1-76

Cement circulated A Trace No. of Sacks None

Cemented by Halliburton Witnessed by Selan Mermis

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Water 140'

Hole will be filled w/ Ready Mix to surface.