

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

**RECEIVED**  
 NEW MEXICO OIL CONSERVATION COMMISSION  
 SEP 22 1976  
**O. C. C.**  
 ARTESIA, OFFICE

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>B-2071</b>

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>Marbob Energy Corporation</b>	8. Farm or Lease Name <b>N G Phillips State</b>
3. Address of Operator <b>P. O. Box 304, Artesia, N. M. 88210</b>	9. Well No. <b>21</b>
4. Location of Well UNIT LETTER <b>J</b> <b>1630.4</b> FEET FROM THE <b>south</b> LINE AND <b>2286.6</b> FEET FROM THE <b>east</b> LINE, SECTION <b>27</b> TOWNSHIP <b>17 S</b> RANGE <b>28 E</b> NMPM.	10. Field and Pool, or Wildcat <b>East Empire Yates - SR</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3663 GR</b>	12. County <b>Eddy</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <b>cementing surface casing</b> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**TD 898'**

Ran 892' used 7 5/8" 26.40# K-55 casing, insert float shoe, Halliburton cemented with 225 sx lite and 100 sx Class C 50/50 pozmix, trace cement to surface, fell back, filled to surface with 7 yards ready mix.  
 Drilled 565' with 12" hole  
 " 333' with 9" hole

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Donathy Hammond* TITLE agent DATE 9/20/76  
 APPROVED BY *W. A. Gressett* TITLE SUPERVISOR, DISTRICT II DATE SEP 22 1976  
 CONDITIONS OF APPROVAL, IF ANY: