NO. OF COPIES RECEIVED 3	Form C-103
DISTRIBUTION	Supersedes Old
SANTA FE // NEW MEXICO OIL CONSERVATION COMMISSIONE D	C-102 and C-103 Effective 1-1-65
FILE //	FUECTIAN 1-1-02
U.S.G.S. AUG 1 0 1976	Sa. Indicate Type of Lease
LAND OFFICE	State Fee X
OPERATOR /	5. State Oll & Gas Lease No.
0. C. C.	
BUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DAILL OR TO DEEDEN OR DUG DACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
DIL CAS OTHER-	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Yates Petroleum Corporation	Gissler "AV"
3. Address of Operator	9. Well No.
207 South 4th Street - Artesia, NM 88210	14
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER F. 1650 FEET FROM THE NORTH LINE AND 1650 FEET FROM	Eagle Creek S.A.
THE West LINE, SECTION 23 TOWNSHIP 175 RANGE 25E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3506° GR	12. County Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
NOTICE OF INTENTION TO: SUBSEQUENT	
PERFORM REMEDIAL WORK	
TEMPORARILY ABANDON	ALTERING CASING
PULL OR ALTER CASING	FEUG AND ABARDONMENT
OTHER	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including e work) SEE RULE 1103 Spudded a 15" hole at 6:00 PM 8-3-76. Drilled to 350' and	stimated date of starting any proposed ran 9 joints of
10-3/4" 32# 367' of casing set at 350'. Cemented w/250 sacks	s of Class "C" 4%
CaCl. PD 11:00 AM 8-4-76. Cement circulated. WOC 12 hours	

CaCl. PD 11:00 AM 8-4-76. Cement circulated. WOC 12 hours. Cut of casing, reduced hole to 9-7/8", drilled plug & tested to 600#. OK. Resumed drilling. TD 1175' - Ran 36 joints of 7" 20# K-55 used casing (1176.80') set at 1175' KB, 1-Guide shoe, centralizers at 1142-491', baskets at 524 &458'. Cemented by Denton w/350 sacks of Lite 2% CaCl followed w/150 sacks Class "C" 2% CaCl. PD 2:30 PM 8-6-76. Cement did not circulate. WOC 6 hours and ran Temperature Survey found top of cement at 800'. Ran 1" to 420', spotted 50 sacks of Class "C" 4% CaCl. PD at 10:00 PM 8-6-76. Ran 1" to 420', spotted 50 sacks Class "C" 4% CaCl. PD 1:30 AM 8-7-76. Ran 1" to 378', spotted 50 sacks Class "C" 4% CaCl. PD 4:30 AM 8-7-76. Ran 1" to 399', spotted 50 sacks of Class "C" 4% CaCl. PD 7:30 AM 8-7-76. Ran 1" to 315', spotted 50 sacks of Class "C" 4% CaCl. PD 7:30 AM 8-7-76. Filled hole to surface w/3 yards of Ready-mix at 12:30 PM 8-7-76. WOC 18 hours Nippled up, tested BOP's to 1000#. OK. Reduced hole to 6¹/₄", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete signed <u>Christics</u> mliusan				8-9-76	
APPROVED BY W.A. Gressett CONDITIONS OF APPROVAL, IF ANY:	TITLE	SUPERVISOR, DISTRICT II	DATE	AUG 131976	