

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL AND GAS COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

AUG 27 1976

O. C. C.

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Form or Lease Name Morris Estate "CC"
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		9. Well No. 4
4. Location of Well UNIT LETTER L 1650 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 14 TOWNSHIP 17S RANGE 25E NMPM.		10. Field and Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3496' GR		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 3:00 PM 8-13-76.

TD 356' - Ran 11 joints of 10-3/4" 40# used casing (359.50') set at 356' KB. Cemented by Denton w/200 sacks of Class "C" 4% CaCl. PD 4:45 AM 8-14-76. Cement circulated. WOC 12 hours, cut off casing, reduced hole to 9-7/8", drilled plug and resumed drilling.

TD 1154' - Ran 28 joints of 7" 23# J-55 used casing (1157.05') set at 1154' KB. w/Guide Shoe, Centralizers at 1113.22' and 610.75', cement baskets at 653.54' and 567.37'. Cemented by Denton w/350 sx of lite 2% CaCl followed w/150 sx of Class "C" 2% CaCl. PD 12:00 noon 8-16-76. Cement did not circulate. WOC 6 hrs. ran Temp Survey, found top of cement at 550'. Ran 1" to 478', spotted 50 sacks of Class "C" 4% CaCl. PD 7:00 PM 8-16-76. Ran 1" to 357', spotted 50 sacks of Class "C" 4% CaCl. PD 9:30 PM 8-16-76. Ran 1" to 315', spotted 50 sacks of Class "C" 4% CaCl. PD 12:15 AM 8-17-76. Ran 1" to 295', spotted 50 sacks of Class "C" 4% CaCl. PD 3:30 AM 8-17-76. Cement circulated but fell back, filled hole to surface w/6 yards of Ready-Mix. WOC 18 hours nipples up, tested BOP's to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 8-26-76

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 30 1976

CONDITIONS OF APPROVAL, IF ANY: