

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Petr Corp.</u>		Lease <u>Mc Cow B+</u>		Well # <u>5</u>	
Location of Well	Unit <u>A</u> <u>380N</u> <u>940E</u>	Section <u>14</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>Byrd</u>		Type of Equipment <u>Blair</u>		

APPROVED CASING PROGRAM

* witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32		300	line
9 7/8"	7"	20-23		1150	"
6 1/4"	4 1/2" + 5 1/2"	9.5 + 15.5		1500	125

Casing Data:

Int: Surface 37 joints of 7" inch 23 # Grade Unal API N-80

(Approved) (Rejected)

Inspected by Selan Mearns date 9-3-76

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required 500/sx

Type of Shoe used Guide Float collar used None Btm 2 jts welded Threadlock

TD of hole 1215 KB Set 1202' 0" Feet of 7" Inch 23 # Grade N-80

New-used csg. @ 1202' 0" with 150 sacks neat cement around shoe Class C 2 1/2 cc
+ 350 sax class C mix additives 2 1/2 cc

Plug down @ 11:30 AM (AM) (PM) Date 9-4-76

Cement circulated Yes No. of Sacks 35/sx

Cemented by Deaton Witnessed by Selan Mearns

Temp. Survey ran @ (AM) (PM) Date (AM) (PM) top cement @ (AM) (PM)

Casing test @ (AM) (PM) Date (AM) (PM)

Method Used (AM) (PM) Witnessed by (AM) (PM)

Checked for shut off @ (AM) (PM) Date (AM) (PM)

Method used (AM) (PM) Witnessed by (AM) (PM)

Remarks: Surface: 15" hole TD 334' KB Ran 9 1/2" 10 3/4" 40' used

Cent 175/sx Class C 4 1/2 cc PD 5:00 AM 9-2-76, Did not rise

Hole filled w/Ready Mix

Water 350-654, 682-712, 932-1099