

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions
verse side)copy to SF
Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 12832

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a depth of 100 feet or more.
Use "APPLICATION FOR PERMIT TO DRILL" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Yates Petroleum Corporation		8. FARM OR LEASE NAME Federal "CD"	
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, N.M. 88210		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FNL & 1650' FWL of Sec. 28-17S-25E		10. FIELD AND POOL, OR WILDCAT Eagle Creek (S.A.)	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3570' GR	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input checked="" type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	(Other) <input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 1141' - Ran 26 joints of new 7" 20# J-55 ST&C (1143.33') of csg. set at 1141' KB. 1-Guide shoe, centralizers at 1125.80' & 845.02', cement basket at 798.24'. Cemented by Denton w/400 sacks of Class C w/30% by volume, Stratocrete & 2% CaCl followed w/150 sacks of Class c 2% CaCl. PD 4:00 AM 10-5-76/ Cement did not circulate. Ran Temperature Survey at 10:15 AM 10-5-76, found top of cement at 950'. W/1" at 693' spotted 50 sacks of Class C 4% CaCl. PD 1:00 PM 10-5-76. Ran 1" and tagged top of cement at 622', w/1" at 609' spotted 75 sacks of Class C 4% CaCl. PD 5:15 PM 10-5-76. Ran 1" and tagged cement at 504', w/1" at 483' spotted 75 sacks of Class C 4% CaCl 1% flocele. PD 9:30 PM 10-5-76. Ran 1" and tagged cement at 420', w/1" at 399', spotted 75 sacks of Class C 4% CaCl 1% flocele. PD 1:00 AM 10-6-76. Ran 1" and tagged cement at 410', w/1" at 378', spotted 50 sacks of Class C 4% CaCl 1% flocele. PD 4:30 AM 10-6-76. Ran 1" and tagged cement at 349', w/1" at 315', spotted 50 sacks of Class C 4% CaCl 1% flocele. PD 7:45 AM 10-6-76. Ran 1" and tagged cement at 328', w/1" at 315', spotted 50 sacks of Class C 4% CaCl. PD 10:45 AM 10-6-76. Tagged cement at 325', w/1" at 315', spotted 50 sacks of Class C 4% CaCl. PD 2:00 PM 10-6-76. Stuck 1" pipe, had fluid returns to surface. Spotted 20 sacks of Class C 4% CaCl. Backed off 1", leaving 7 jts of 1" in hole (147'). RIH & tagged

18. I hereby certify that the foregoing is true and correct

(Continued on Attached Page)

SIGNED

TITLE

Geol Secty

DATE

10-15-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

OCT 16 1976

CONDITIONS OF APPROVAL, IF ANY:

Yates Petroleum Corporation
207 So. 4th Street - Artesia, NM
Federal "CD" No. 3 - NM 12832
Section 28-17S-25E, Eddy County, NM

(Continued)

top of cement at 224', w/1" at 175', spotted 60 sacks of 4% CaCl at 3:00 PM 10-6-76. Had contaminated cement returns to surface. WOC 3 hours, until 6:00 PM 10-6-76, tagged cement to 266'. WOC 3 hours, until 9:00 PM 10-6-76, tagged cement at 247'. W/1" at 231', spotted 65 sacks of Class C 4% CaCl. Cement circulated. PD at 11:00 PM 10-6-76. WOC 18 hours, NU, tested BOP's to 1000#. OK. Reduced hole to 6¼", drilled plug and tested to 600#. OK. Resumed drilling.