

U. S. GEOLOGICAL SURVEY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIP.
(Other instructions
verse side)Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 660

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "GR"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

W. Id. 1

Undesignated
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25-17S-24E

Unit E NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

JAN 18 1977

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

O.C.C.
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2050' FNL & 660' FWL of Section 25-17S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3691 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Plug back & set Prod. csg

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8200'; PBTD 7589'. WIH open ended to plug back w/4½" DP and spotted 50 sack plug of Class H cement at 7800-7650'. COH and layed down DP & DC. Ran 238 joints of 4½" casing as follows: Ran 4½" 11.6# K-55 ST&C (600') and 4½" 10.5# K-55 ST&C (7021') (Total 7621' of casing) set at 7621', 1-Guide shoe at 7621', float collar at 7589' and 11 centralizers. Cemented w/500 gallons of mud flush, 170 sacks of Class H + 5# KCL & 6% CFR2 followed w/225 sacks of Halli-Lite w/5# KCL tailed in w/500 sacks of Class H + 5# KCL & 6% CFR2. (Slurry 15.6) PD 11:00 PM 11-27-76. WOC and tested to 1500#. OK. Top of cement 5112'.

RECEIVED

JAN 17 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christina Tomlinson

TITLE

Geol. Secty

DATE 1-16-77

(This space for Federal or State office use)

APPROVED BY

J. D. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE JAN 17 1977

CONDITIONS OF APPROVAL, IF ANY: