

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

DEC 21 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation	5. State Oil & Gas Lease No.
3. Address of Operator 207 South Fourth Street - Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER C 835 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 17S RANGE 26E NMPM.	8. Farm or Lease Name Tom Brown "GO" Conn
15. Elevation (Show whether DF, RT, GR, etc.) 3339' GR	9. Well No. 1
	10. Field and Pool, or Wildcat Und. Kennedy Farms Morrow
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 8:00 p.m. 12-10-76.
TD 402'. Ran 11 joints of 13-3/8" 61# (403') casing set at 402'. Cemented w/300 sacks Class "C" 4% CaCl. PD 3:30 a.m. 12-11-76. WOC 12 hours. Nipped up. Reduced hole to 12¼" and resumed drilling. TD 1402'. Ran 35 joints of 8-5/8" 24# K-55 (1403') set at 1402'. 1-Guide Shoe, 2 centralizers, and basket. Cemented w/400 sacks of Halli-Lite w/5# gilsonite, ¼# flocele/sx 2% CaCl followed w/200 sacks of Class "C" 2% CaCl. PD 2:30 a.m. 12-13-76. Cement did not circulate. WOC 6 hours and ran Temperature Survey, found top of cement at 275'. Filled hole w/5 yds of Ready-Mix. WOC 18 hours. Nipped up and tested BOP's to 1500#. OK. Reduced hole to 7-7/8", tested casing to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geological Secretary DATE 12-20-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE DEC 21 1976

CONDITIONS OF APPROVAL, IF ANY: