

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanson Operating Company, Inc.

3. Address and Telephone No.

P.O. Box 1515, Roswell, NM 88202-1515

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 28, T. 16S, R. 30E 660' FSL & 660' FEL

5. Lease Designation and Serial No.

NM14900

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. FEDERAL

Square Lake #1

9. API Well No.

30-015-21965

10. Field and Pool, or Exploratory Area

Square Lake

11. County or Parish, State

Eddy, New Mexico

12 CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Hanson Operating Company, Inc. is proposing to plug & abandon the above well in the following manner:

1. Cut off & pull 8 5/8" casing at 1300' (top of cement), set a 100' cement plug at top of Yates formation.
2. Set a 50' cement plug at surface.
3. Set cement plug 100' above perfs at 2859'
4. Remove all equipment, install dry hole marker & restore location. All plugs will be set in place using 9.5# mud laden fluid, all cement plugs will be Class C cement.

14. I hereby certify that the foregoing is true and correct

Signed Betsy Spier

Title Prod. Analyst

Date 12-9-99

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side