

N. M. O. C. C. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

copy to SF

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-1135-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "JL"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 14-T14S-R28E

12. COUNTY OR PARISH

Eddy

N.M.

1. OIL ☐ WELL GAS ☐ WELL OTHER ☒ Dry Hole AUG 23 1977

2. NAME OF OPERATOR McClellan Oil Corp. ✓ O.C.C.

3. ADDRESS OF OPERATOR ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface Box 848, Roswell, New Mexico 88201

990' FNL & 1750' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3546' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/30/77: Verbal permission was given this date by the District Engineer, Artesia, N.M. to plug and abandon this test as follows:

T.D. 1870'. No fluid at total depth.
Salt water at 1608-1613 (Grayburg)
No definitive salt section was drilled.

Heavy mud at bottom of hole to 1650'
100' cement from 1550' to 1650'.
Heavy mud from 1550' to 350'
100' cement plug 250' to 350'.
20 cement plug at surface.

Install dry hole marker and restore surface to as near its original state as possible.
300' of 10" casing will be pulled.
1645' of 7" casing will be pulled.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. J. McClellan TITLE Operator

DATE 7/1/77

(This space for Federal or State office use)

APPROVED BY

J. L. Lora TITLE ACTING DISTRICT ENGINEER

DATE AUG 26 1977

CONDITIONS OF APPROVAL, IF ANY:

subject to rigging drill and access road not used!

*See Instructions on Reverse Side

RECEIVED

JUL 05 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO