

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(See other instructions on reverse side)

Copy to SF
Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR

Hanson Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 1515, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with instructions on reverse side)

At surface 330' FSL and 1650' FEL

At top prod. interval reported below

At total depth

O. C. C.
ARTESIA, OFFICE

DATE ISSUED

15. DATE SPUDDED 2-19-77 16. DATE T.D. REACHED 2-26-77 17. DATE COMPL. (Ready to prod.) 3-15-77 18. ELEVATIONS (OF, RKB, RT, GR, ETC.)* 3751.6 G. L. 19. ELEV. CASINGHEAD 3130'

20. TOTAL DEPTH, MD & TVD 3148 21. PLUG, BACK T.D., MD & TVD ----- 22. IF MULTIPLE COMPL., HOW MANY* ----- 23. INTERVALS DRILLED BY ----- ROTARY TOOLS 0-3148 CABLE TOOLS -----

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

Premier 2930' - 2954'

San Andres 3040' - 3048'

25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN

Compensated Densilog Neutron, Cement Bond Log and Gamma Ray Tie-in Log

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	28#	490.60'	12 1/4"	225 sx. Class "C"	NONE
5 1/2"	15.5#	3130'	7 7/8"	350 sx. 50/50 pozmix	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	2880'	NONE

31. PERFORATION RECORD (Interval, size and number)

2930' - 2938' 2 shots per foot

2940' - 2944' 2 shots per foot

2952' - 2954' 2 shots per foot

3040' - 3048' 2 shots per foot

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
2930' - 2954'	1500 Gallons NE Acid and 15M# Sand
3040' - 3048'	1500 Gallons NE Acid and 26M# Sand

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
3-17-77		Pumping w/ 2" X 1 1/2" X 12'				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
3-18-77	24	---	→	27	1	18	3704 - 1
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
-----	-----	→	27	1	18	39	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Flared

TEST WITNESSED BY

Clyde Bratcher

35. LIST OF ATTACHMENTS

Compensated Densilog Neutron, Cement Bond Log and Gamma Ray Tie-in Log

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

Ray Miller

TITLE Vice Pres. Production

DATE 3/18/77

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS	
				NAME	MEAS. DEPTH
				Yates	1330'
				Seven Rivers	1418'
				Queen Sand	2178'
				Premier	2922'
				San Andres	2960'
				T. D.	3150'