

Form 8160-5
(November 1985)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

45f

SEP 19 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ARTESIA, OFFICE

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 S. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980 FNL & 660 FEL, Sec. 28-16S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3722' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 0559535

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal FR

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Square Lake-Grayburg-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit H, Sec. 28-T16S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☒
☒
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Perforate San Andres

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-12-85. WIH and perforated 3542-3658' w/13 .42" holes as follows: 3542, 60, 60½, 91, 96½, 3612, 18, 27, 29, 35, 47, 56 and 58'. Treated perms 3542-3658' w/2000 gals 15% NEFE acid and ball sealers. WIH and perforated 3540-3657' w/18 .42" holes as follows: 3540, 44, 59, 61, 73, 93, 95, 3610, 14, 16, 20, 26, 28, 30, 36½, 48, 55 and 57'.

7-13-85. Frac'd (via 2-7/8" tubing) perms 3542-3658' (13 holes) and 3540-3657' (18 holes) w/40000 gals gelled KCL water, 60000# 20/40 and 20000# 12/20 sand, 2000 gals 15% NEFE acid. Flowed well back. Set pumping equipment. Returned well to production.

Well producing from perforations 2978-3013, 3540-3658'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Quanita Goodlett

TITLE

Production Supervisor

DATE

9-12-85

(This space for Federal or State office use)

APPROVED BY

COPIED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 17 1985

*See Instructions on Reverse Side