

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>C.E. Lauer + B.N. Muncy Jr.</i>		Lease <i>State B</i>		Well # <i>2</i>	
Location of Well	Unit <i>9905 330W</i>	Section <i>27</i>	Township <i>17</i>	Range <i>28</i>	County <i>Eddy</i>
Drilling Contractor <i>J.B. Adamson</i>		Type of Equipment <i>Cable tools to start approx. 3-10-77</i>			

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
8"	7"	20		500	Set & pulled
6"	4 1/2"	10.5		850	200 lin.

Casing Data:

Surface 27 joints of 4 1/2 inch 10 # Grade J-55  
(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 7 1/2 Size of Casing 7 Sacks cement required 200

Type of Shoe used Guide Float collar used 110 Btm 3 jts welded Yes

TD of hole 823 Set 275 Feet of 4 1/2 Inch 10 # Grade J-55

New-used csg. @ 200 with 100 sacks neat cement around shoe

+ 200 sax Donnell light additives 5/100 of 1% D-60 w/ 50# Cellulose

Plug down @ 2:45 (AM) (PM) Date 5/4/77

Cement circulated 15 No. of Sacks

Cemented by Donnell Witnessed by M. J. Williams

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: Top of cement @ 25' - Filled w/ 1 1/2 yds of Redi-mix

8 5/8" Csg. left in hole from 20' to 25'