

**NMOCC COPY**  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL  
(Other instructions  
verse side)

E-  
re-

*Copy to SF*  
Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 2346

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Robinson "HW" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA Unit K NMPM

Sec. 25-16S-24E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL ☒ GAS ☐ OTHER ☐

AUG 16 1977

2. NAME OF OPERATOR

Yates Petroleum Corporation

B.C.C.

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

1980' FSL & 1980' FWL of Sec. 25-16S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3638' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

Plug back & set casing

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 7116' - Plugged back 6662-6500 w/50 sacks of Class C cement.  
Ran 203 joints of 4½" 10.5# K-55 (6478') of casing. Diff -fill collar at 6466' and shoe at 6478'. 6-centralizers at 6412, 6320, 6238, 5092, 4996, 4904. Cemented as follows: 200 sacks of Class C + .5% CFR-2 + 3#/sx KCL. Followed w/280 sacks of HL + .5% CFR-2 + 3#/sx KCL tailed in w/120 sacks of Class C + .5% CFR-2 + 3#/sx KCL. PD 4:45 PM 6-16-77.  
Ran Temperature Survey and found top of cement at 3800'. WOC and tested to 1500#. OK.

RECEIVED

AUG 11 1977

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Tomlinson*

TITLE

Geol. Secty

DATE

8-11-77

(This space for Federal or State office use)

TITLE

DATE

APPROVED

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

AUG 14 1977

H. L. ...  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side