

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Texas Pacific Oil Co. Inc.</i>		Lease <i>Glen Farmer</i>		Well # <i>1</i>	
Location of Well	Unit/H <i>1980S+W</i>	Section <i>26</i>	Township <i>17</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Art Dwyer Co.</i>		Type of Equipment <i>Pottery to start?</i>			

APPROVED CASING PROGRAM

* witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>26</i>	<i>20</i>	<i>59 Foot</i>	<i>40</i>	<i>40</i>	
<i>17 1/2"</i>	<i>13 3/8</i>	<i>48</i>		<i>550</i>	<i>600 c/c</i>
* <i>12 1/4"</i>	<i>8 7/8</i>	<i>24</i>		<i>1500</i>	<i>800 "</i>
<i>7 7/8"</i>	<i>5 1/2"</i>	<i>15.5 + 17</i>		<i>8900</i>	

Casing Data:

Surface *39* joints of *8 5/8* inch *24* # Grade *API New K-55 STD*
(Approved) (Rejected)

Inspected by *Sam McManis* date *6-28-77*

Cementing Program

Size of hole *12 1/4"* Size of Casing *8 5/8* Sacks cement required *800/sx*

Type of Shoe used *Cush* Float collar used *Yes* Btm *3* jts *waited Thread/Lock*

TD of hole *1500 KB* Set *14286* Feet of *8 7/8* Inch *24* # Grade *K-55*

New-used csg. @ *1488 GL* with *300/* sacks neat cement around shoe *Class C 2 1/2-c*
+ *500/* sack *Dwell Life w/* additives *1/4" Cello Flakes 2% c-c*

Plug down @ *4:00 (AM) (PM)* Date *6-29-77*

Cement circulated *No* No. of Sacks *None*

Cemented by *Danell* Witnessed by *Sam McManis*

Temp. Survey ran @ *10:30 (AM) (PM)* Date *6-29-77* top cement @ *6:20 By Hanna Tool*

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Water 108-30, 137-49, 149-550, 550-795, 994-1004, 1046-62*
1225-1323, 1333-41, (1351-54 P)

Ran 1" 558 Tased, Cnt 75/50 Class C 4 1/2 cc PD 3:00 PM

Ran 1" 550 Tased, Cnt 175/50 Class C 4 1/2 cc PD 5:45 PM

Ran 1" 6 150 Tased, Cnt 50/50 Class C Neat PD 8:10 PM

Circ 5/5x