

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-actively logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured for this. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 54 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 110.5.

Northwestern New Mexico

Northwestern New Mexico

Oil or Gas Sands or Zones

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	fect.
No. 2, from	to	fect.
No. 3, from	to	fect.
No. 4, from	to	fect.

Formation

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	130	130	Surface & Red Bed	5675	5720	45	Sand & Lime
130	480	350	Red Bed & Anhy	5720	5855	135	Lime
480	965	485	Anhy & Salt	5855	6030	175	Dolo
965	1050	85	Anhy	6030	6319	289	Sand & Dolo
1050	1235	185	Anhy & Gyp				
1235	1890	655	Lime				
1890	2075	185	Sand & Shale				
2075	2670	595	Lime				
2670	3850	1180	Dolo				
3850	4095	245	Sand & Lime				
4095	4156	61	Dolomite				
4156	4255	99	Sand & Lime				
4255	4375	120	Dolomite				
4375	4475	100	Sand & Lime				
4475	4670	195	Dolo				
4670	4740	70	Lime				
4740	5675	935	Dolo				