

## SUPPLEMENTARY SHEET FOR F. R. # 06006 D

PAGE # 7

## SURFACE DATA

DESCRIPTION (RATE OF FLOW)	' TIME	PRESSURE (P.S.I.G.)	Surface Choke
OPENED TOOL	0732	.352	CLOSED
51 MSCF/DAY			
21427 MSCF/DAY	0734	499	1.1
22138 MSCF/DAY	0736	1519	1.1
CLOSED FOR INITIAL SHUT-IN	0738	2231	1.1
FINISHED SHUT-IN	0906	1847	1.1
RE-OPENED TOOL	0908	1848	1.1
243 MSCF/DAY			
15692 MSCF/DAY	0910	2483	1.1
OPENED ON SURFACE	0911	2650	1/4**
3994 MSCF/DAY			
4078 MSC/DAY	0914	2710	1.1
CLOSED FOR SURFACE	0915	2868	CLOSED
OPENED ON SURFACE	0918	2546	1/2"
16353 MSCF/DAY			
13938 MSCF/DAY	0930	2163	1 1
13820 MSCF/DAY	0940	2145	• •
CLOSED ON SURFACE	0941	2531	CLOSED
OPENED ON SEPARATOR	0954	2770	36/64"
CLOSED ON SURFACE TO ADJUST SEPARATOR	1008		* *
OPENED TO SEPARATOR	1023	_	11
13200 MSCF/DAY FOR 1 HOUR	1041	2050	1 1
CLOSED FOR FINAL SHUT-IN	1208	<u> </u>	5 T.
FINISHED SHUT-IN	1610	_	1.1
PULLED PACKER LOOSE	16/2	<del>-</del> .	_
STARTED REVERSING	1639	-	·
FINISHED REVERSING	1653	- · · · ·	-