

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Bearings Service Supply Co. Inc.</u>		Lease <u>MWJ State</u>		Well # <u>1</u>	
Location of Well	Unit <u>1650 N</u> <u>990 W</u>	Section <u>10</u>	Township <u>17</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor <u>Artesia Fishing Tool Co.</u>	Type of Equipment <u>Rotary</u> to start <u>11-15-77</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11"</u>	<u>8 5/8"</u>	<u>24</u>		<u>400</u>	<u>125 cms</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>2200</u>	<u>550 cms</u>

Casing Data:

Surface 10 joints of 8 5/8 inch 24 # Grade API New J-55
(Approved) (Rejected)

Inspected by Alan Merriam date 11-17-77

Cementing Program

Size of hole 11" Size of Casing 8 5/8 Sacks cement required 175/5X

Type of Shoe used Guide Float collar used None Btm 2 jts welded Thread-Lock

TD of hole 4270 Set 420 Feet of 8 5/8 inch 24 # Grade J-55

New-used csg. @ 420 GL with 175 sacks neat cement around shoe Class C 2% CC
+ sax additives

Plug down @ 2:10 (AM) (PM) Date 11-17-77

Cement circulated Yes No. of Sacks 55/5X

Cemented by Halliburton Witnessed by Alan Merriam

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: