

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved *copy 1007*
Budget Bureau No. 42-R1424.

LEASE DESIGNATION AND SERIAL NO.

NM-9987

IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

UNIT AGREEMENT NAME

N/A

NAME OF LEASEE

Exxon Federal

WELL NO.

1

FIELD AND POOL, OR WILDCAT

Wildcat Had. St.

SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

29, T-16-S, R-29-E

COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

SEP 28 1978

D. C. C.
ARTESIA, OFFICE

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Carl A. Schellinger ✓

3. ADDRESS OF OPERATOR
P.O. Box 447, Roswell, N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
~~1980' FNL & 1980' FEL~~
660/S 660/W

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3636.6 GP

12. COUNTY OR PARISH 13. STATE
Eddy NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/5/78 TD 2407', Ran 60 joints 4 1/2" 9.5 lb. casing to 2407' cemented with 425 sacks of Class C, 50/50 pos, 2% gel, 1/4 lb. flow seal per sack, plug down @ 9:45 P.M. 8/5/78.

8/22/78 TD 2407'; Ran Gamma-ray Collar Log, Perforated 2360-2370, 2372-2378, 2389-2394, w/2SPF. Ran Howco R-4 Packer and 74 jts. of 2 3/8" tubing, set @ 2321.21. Swab down, good show gas.

8/23/78 Acidized 1500 gal. 15% DS-30 acid, Max. pressure 2500#. Treating pressure 1500#. Swab down, no increase in gas.

8/25/78 Loaded hole, released pkr. and pulled tubing. Frac. down 4 1/2" casing with 20,000 gal. 3% gel acid and 19,000# 20/40 sand.

18. I hereby certify that the foregoing is true and correct

SIGNED

Carl A. Schellinger

TITLE Operator

DATE 9/11/78

(This space for Federal or State office use)

APPROVED BY

Lee D. Lara

TITLE ACTING DISTRICT ENGINEER

DATE SEP 28 1978

CONDITIONS OF APPROVAL, IF ANY: