

- F. Current laws and regulations pertaining to the disposal of human waste will be complied with.
 - G. Trash, waste paper, garbage and junk will be buried in a separate trash pit and covered with a minimum of 24 inches of dirt. All waste material will be contained to prevent scattering by the wind.
 - H. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations.
8. ANCILLARY FACILITIES.
- A. None required.
9. WELLSITE LAYOUT.
- A. Exhibit IV shows the relative location and dimensions of the well pad, reserve pits, and major rig components.
 - B. Only minor leveling will be required to construct the location. The ground surface at the wellsite is relatively flat, with only very minor undulations and a gradual upward slope from west to east. It is estimated that a cut of approximately $1\frac{1}{2}$ feet will be required in the southwest portion of the pad area and a cut of approximately 3 feet, in the southeast portion of the pad area. The pad surface will be covered with six inches of compacted caliche.
 - C. The reserve pits will be plastic lined.
 - D. The pad and pit area has been staked and flagged.
10. PLANS FOR RESTORATION OF THE SURFACE.
- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. Pits will be filled and the location cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing a condition as possible.
 - B. Any unguarded pits containing fluids will be fenced until they have been filled.
 - C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.