

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 22 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation ✓	5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER H, 2510 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 33 TOWNSHIP 17S RANGE 26E NMPM.	8. Farm or Lease Name Kennedy "JQ" Com
15. Elevation (Show whether DF, RT, GR, etc.) 3339' GR	9. Well No. 1
	10. Field and Pool, or Wildcat Und Kennedy Farms Morro
	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Set Production Casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 211 joints of 4½" 10.5# and 11.6# of N-80 ST&C casing as follows: 50 joints 11.6# (2050'), 132 joints 10.5# (5489'), 29 joints 11.6# (1189') (Total 8728') set at 8728'. 1-Guide shoe at 8728', Diff-Fill Collar at 8687'. 7-centralizers at 8787, 8750, 8570, 8410, 8320, 8110 and 8080'. Cemented w/250 gallons of mud flush, 435 sacks of Howco Lite 5#/sack KCL 6/10% CFR-2, 135 sacks of Class H 5#/sack KCL 6/10% CFR-2. PD 3:45 AM 6-20-78. Set slips, tested to 2000#. OK. WOC. Ran Temperature Survey and found top of cement at 6390', WLPBTD at 8666'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Johnson TITLE Geol. Secty DATE 6-21-78

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 23 1978

CONDITIONS OF APPROVAL, IF ANY: