<u>ا</u>			
NO. OF COPIES ALCEIVED 3 DISTRIBUTION RECEIVED	Form C-103 Supersedes Old		
SANTA FE // NEW MEXICO OIL CONSERVATION COMMISSION	C-1 02 and C-103 Effective 1-1-65		
FILE JAN 2 5 1979	P		
U.S.G.S.	Sa. Indicate Type of Lease State Fee X		
LAND OFFICE D. C. C.	State Fee X		
OPERATOR / ARTEBIA, OFFICE			
SUNDRY NOTICES AND REPORTS ON WELLS			
(DO NOT USE THIS FORM FOR FOR FOR FOR DELL OF TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			
	7. Unit Agreement Name		
WELL WELL OTHER- 2. Name of Operator Image: Construction	8. Farm or Lease Name		
Yates Petroleum Corporation	Niles "KA" Com		
3. Address of Cretator	9. Well No.		
207 South 4th Street - Artesia, NM, 88210	1 1 10. Field and Pool, or Wildcat		
4. Location of Well N 660 FEET FROM THE South 1980 FEET FROM THE	1 · · · ·		
UNIT LETTER FEET FROM THE FEET FROM			
THE West Line, Section 24 TOWNSHIP 175 RANGE 24E NMPM.			
15. Elevation (Show whether DF, RT, GR, etc.) 3676' GR	12. County Eddy		
Check Appropriate Box To Indicate Nature of Notice, Report or Oth NOTICE OF INTENTION TO:	ref Data		
PERFORM REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ABANDON	PLUG AND ABANDONMENT		
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	squeeze		
OTHER	[]		
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	activated data of starting any wayneed		
work) SEE RULE 1703.			
TD 8186'; PBTD 8112'. Displaced hole w/KCL water. Ran CBL			
cement at 7810-8106'. WIH & perf. 7825' w/2 holes. RIH w/			
Attempted to circulate and could not circ. Pulled pkr out 8090' w/2 holes. Set retainer at 8078' and cmtd w/75 sx of			
5#/sx KCL. Reversed out 1 bbl of cmt. Squeezed to 2000#.			
found top of cement at 7825'.RIH w/Csg Gun and perf (Miss)			
.41" holes (2spf). RIH w/Guiberson Uni VI pkr and Vent Ass			
8000'. Annulus on vacuum. Ck plug OK. Press up on annulus			
POOH LD pkr and Vent Assembly. RIH w/Rtts pkr resqueezed			
50 sx Class H 4% CFR-2 and 2% Halad-22. Sqzd to 4000#. WOC	-		
cleaned out to 8072'. WIH w/Guiberson Uni VI pkr on 2-3/8	" tbg, set pkr at		
8006'. Trtd perf 8044-8050' w/2000g 20% DS-30 acid & nitro	gen w/ball sealers.		
Swbd dry. Loaded hole and unseated pkr. WIH and set CIBP a	—		
er of cement on top of plug./WOC. WIH w/Csg Gun on wirelin			
7661-7700' w/22 .32" holes (2spf). 7661-64' (6 holes); 767			
7695-7700' (10 holes). WIH w/Guiberson Uni VI pkr on 2-3/	_		
7636'. Trtd perf w/2000g 15% MS acid and nitrogen w/ball s			
18. I hereby certify that the information above is true and complete to the best of my knowledge and helief. (CONT	a on accached page)		
SIGNED (Lington - Anning TITLE Geol. Secty	1-24-79		
SIGNED L. ALLIGITE THE TITLE TITLE	DATE		
LI P. Supervisor, DISTRICT II	JAN 3 0 1979		
APPROVED BY U. C. KUESSER TITLE	JAR JAR		
CONDITIONS OF APPROVAL, IF ANY:			

.

CONDITION5	OF	APPROVAL.	117	ANY: