

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0439900 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "CR"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Und. Richard Knob

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33-17S-25E

Unit K NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug holes in the ground.
Use "APPLICATION FOR PERMIT—" for such proposals.)

FEB 22 1979

O.C.C.
ARTESIA, OFFICE

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

1980' FSL & 1980' FWL of Section 33-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3564' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set Production casing

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

RD 8476' - Ran 222 joints of 4 1/2" 11.6# and 10.5# K-55 casing as follows: 57 joints 11.6# (1805'), 143 joints 10.5# (5977'), 22 joints 11.6# (706') (Total 8488') set at 8476'. 1-Guide shoe and Diff-fill collar at 8476' & 8-centralizers. Cemented w/250 gallons of mud flush, 400 sacks Howco-Lite w/3% CFR-2 2% Halad 22, 3#/sack KCL, 125 sacks Class "H" w/3% CFR-2 2% Halad 22, 3#/sack KCL. Displaced w/40 bbls 2% KCL water. PD 12:30 PM 1-18-79. WOC 8 hours and ran temperature survey and found top of cement at 6110'. Tested to 1500#. OK.

RECEIVED
FEB 22 1979
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Geol. Secty. TITLE Geol. Secty.

DATE 2-22-79

(This space for Federal or State office use)

APPROVED BY ACTING DISTRICT ENGINEER TITLE ACTING DISTRICT ENGINEER

DATE FEB 22 1979

CONDITIONS OF APPROVAL, IF ANY: