## N.M.O.C.D. COPY

Form 9-331 (May 1963)

## UNI ) STATES SUBMIT IN TRIPLIC DEPARTMENT OF THE INTERIOR (Other Instructions of verse side)

GEOLOGICAL	SURVEY
GEOLOGICAL	SURVEI

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.)

MELT RETT X OTHER NAME OF OPERATOR

**JUN** 25 1979

Mesa Petroleum Co ADDRESS OF OPERATOR

O. C. C. 1000 Vaughn Building/Midland, Texas 7970 ARTESIA, OFFICE

TOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface

Unit F, 1980' FNL and 1980' FWL

15, ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO.

3592.2 GR

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 11-T16S-R27E

10. FIELD AND POOL, PRIWILDCAT

ald many

12. COUNTY OR PARISH | 13. STATE New Mexico

Form approved, Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NM 7066

7. UNIT AGREEMENT NAME

S. FARM OR LEASE NAME.

Wells Federal

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF	INTENTION TO:	į
TEST WATER SHUT-OFF	PULL OR ALTER CASING	
FRACTURE TREAT	MULTIPLE COMPLETE	
SHOOT OR ACIDIZE	ABANDON*	
REPAIR WELL	CHANGE PLANS	
(Other)		

SUBSEQUENT REPORT OF: WATER SHIT-OFF REPAIRING WELL PRACTURE TREATMENT ABANDONMENT\* SHOOTING OR AUDIZING (Other) Spudded & 13-3/8" casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

to impression or recompletion report and Log form.)

17. Suscribe proposed or completions (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well at 8:30 on June 16, 1979, drilled 17-1/2" hole to 364'. Ran 9 joints 13-3/8" 54#, ST&C (374.45'), set at 364' RKB. Cemented with 400 sacks Class "C" + 2% cc. P.D. at 1:15 PM. Circulated 100 sacks to pit. WOC 21-1/4 hours. Tested casing to 600 psi, 30 min, ok. Reduced hole to 11" and drill ahead.

## RECEIVED

JUN 20 1979

U.S. GEOLOGICAL SURVEY ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE	Agent		DATE	6-19-79
		<u>.</u>	RICT-ENGINEER	DATE	JUN 22 1979

\*See Instructions on Reverse Side