

13 3/8" at 360' w/360 sx
8 5/8" at 1274' w/1120 sx
5 1/2" at 8031' w/550 sx

TP (Marrow) Perf's 8467-97¹ F 2710 MCFGPD. Pot based on
24 hr test thru 1/2¹ chk. GOR (NR); gty (NR); CP Pkr; TP
420[#]

Capiron #15	DEPTH 3422' CL	PD 8600' RT
-------------	----------------	-------------

F.R. 12-25-78
(Morrow)

1-3-79	Drig	1274'
1-8-79	Drig	3500'
1-15-79	Drig	3705'
1-22-79	Drig	7845'
1-29-79	Drig	6820'

DSR (Gborrow) 8418-90', op 1 hr 30 mins,
rec 200' GCDF, 1 hr 30 min ISIP 3185#, FP
85-1234, 3 hr FSIP 3430#, HP 4110-4110#
BHT 138 deg

2-5-79 TD 8942'; PBD 8928'; WOCU
3-12-79 TD 8942'; PBD 8928'; Complete
Perf (Morrow) 8467-97' w/2 SPF
Acid (8467-97') 1000 gals (7 1/2%)
Frac (8467-97') 23,500 gals + sd
LOG TOPS: San Andres 857', Abo 4245',

3-3-7 NM

EDDY
YATES PETROLEUM CORP.

Eagle Creek, E.
2 Patterson "EL"
Sec 31, T17S, R26E

NM
Page 7.

3-12-79

Continued

Wolfecamp 5404', Cisco 6510', Canyon
7416', Atoka 8240', Morrow 8444', Chester
8657', Mississippian 8810'

LOGS FOR: CNL, FDC, BILL

3-17-79

COMPLETION REPORT

3-8-7 NM
IC 30-015-7040