	· · · ·		· •	Form C-103		
NO. OF COMICS RECCIVED	ļ	<u> 3</u>		Supersedes Old		
DISTRIBUTION			MOIDSHIP OF THE	C-102 and C-103 Effective 1-1-65		
SANTA FE	1		NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-03		
FILE	11	1	DECELVE	Sa. Indicate Type of Lease		
U.S.G.5.	<b> </b>		KECEIVED	State Fco X		
LAND OFFICE				5. State Oil & Gas Lease No.		
OPERATOR	1/	<u> </u>	MAR 2 0 1979			
(DO NOT USE THIS FO	SU PRALES	NDF	RY NOTICES AND REPORTS ON WELLS	7. Unit Agreement None		
I. OIL CAS	, [X	}	OTHER-			
2. Name of Operator			VICE	B. Farm or Lease Name		
2. Name of Operation	Jackson "AT"					
Yates Petro	9. Well No.					
3. Address of Operator			Street - Artesia, NM 88210	1 9		
207 South F	Und. E. Eagle Creek					
4. Location of Well			550 South 660	A+oka-Morrow		
UNIT LETTERM			660 FEET FROM THE South LINE AND 660 FEET FROM	TITTITITI		
1			10N 13 TOWNSHIP 17S RANGE 25E NMPM.			
mmmm	12. County					
			15. Elevation (Show whether DF, RT, GR, etc.)  3465 GR	Eddy ///////		
16.			Appropriate Box To Indicate Nature of Notice, Report or Other Nature of Nature o	ner Data REPORT OF:		
NOT	ICE I	J - 1	A LEW TON TO			
	$\neg$		PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING		
PERFORM REMEDIAL WORK	╡		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT		
TEMPORARILY ABANDON  PULL OR ALTER CASING	<u> </u>		CHANGE PLANS CASING TEST AND CEMENT JOB	n casing X		
	_		отнея 5½" productio	ii Casting		
OTHER	·					
VIII.			Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any propose		
to Describe Drovesed or (	Comple	eted (	Operations (Clearly state all pertinent details, and give pertinent dates, including	•		

TD 8400'. Ran 206 joints of 5-1/2" K-55 17# & 15.5# casing as follows:
TD 8400'. Ran 206 joints of 5-1/2" K-55 17# & 15.5# casing as follows:
Tan 41 joints 17# K-55 LT&C (1583.74'); 154 joints 15.5# K-55 ST&C
(6319.06'); 11 joints 15.5# K-55 LT&C (463.40') and 1 joint 17# K-55
LT&C (40.72') (Total 8406.92') of casing set at 8400'. Ran 13 centralizers
as follows: 8361, 8322, 8281, 8251, 8010, 7969, 7928, 7815, 7425, 7386, 7190,
6645, 6565. Cemented w/250 gallons mud flush, 370 sacks Howco Lite 6% CFR2
+ 3% Halad 22 + 5#/sack KCL. Followed w/150 sacks Class "H" w/6% CFR2 +
3% Halad 22 + 5#/sack KCL. Displaced w/40 bbls 2% KCL. PD 6:45 PM 3-1-79.
WOC 9 hours. Ran Temperature Survey and found top of cement at 5710'.
PBTD 8420' by wireline. Released rig at 10:45 PM 3-1-79.

		•		
		· · · ·		•
•	,			
	•			
-				
		to the and ballet		
hereby certify that the information abov	e is true and complete to the	e best of my knowledge and belief.		
Christine For	Menson TITE	. Geological Secretary	DATE_	3-19-79
		DISTRUT II		MAD 9 1 4070
Will Dies	W TITL	SUPERVISOR, DISTRICT II	DATE_	MAR 2 1 1979
OVED SY		•		
IDITIONS OF APPROVAL, IF ANY	•	·		
	- <b>*</b>			