

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Collier + Collier</u>		Lease <u>State B 1969 Tr. 1</u>		Well # <u>12</u>	
Location of Well	Unit <u>0</u> <u>940 S</u> <u>1650 E</u>	Section <u>22</u>	Township <u>17</u>	Range <u>28</u>	County <u>Sddy</u>
Drilling Contractor	<u>Yucca Dry Co</u>		Type of Equipment		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>6 1/4</u>	<u>4 1/2</u>	<u>9.5</u>	<u>New</u>	<u>800</u>	<u>250</u>
Casing Data:					
Surface _____ joints of <u>4 1/2</u> inch <u>9.5</u> # Grade <u>J-55</u>					
<u>Yes</u> (Approved) (Rejected)					
Inspected by <u>B.W. Weaver</u> date <u>2-6-80</u>					
Cementing Program					
Size of hole <u>6 1/4</u> Size of Casing <u>4 1/2</u> Sacks cement required <u>250</u>					
Type of Shoe used <u>Float</u> ^{Shoe} Float collar used <u>—</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>800</u> Set <u>800</u> Feet of <u>4 1/2</u> Inch <u>9.5</u> # Grade <u>K-55</u>					
New-used csg. @ <u>800</u> with <u>250</u> sacks neat cement around shoe					
+ _____ sax _____ additives _____					