NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

	<u>F1</u>	ELD REPORT	FOR CEN	IENTING	<u>; </u>	WELLS				
Operator.	Coller Hollier			Lease B 1969 Jul				Well # /3		
Location of Well	3305 ^{nit} 0 1650e	Section		Township 12		Range	County Elly			
Drilling Contractor Guicea Duly G			- o.	Type of Equipment Folary & start 2-16-79						
APPROVED CASING PROGRAM										
Size of Ho	le Size	of Casing	Weigh For		Ne	w or Used	Depth	Sacks	Cement	
21/8"		41/2"	9	5			800	250		
		₩ ──── ₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩	an ang sa	در در ۲۰۹۲ (می دور در ۲۰۹۲ (می در در ۲۰۹۲ (می در در ۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰۹۲ (۲۰			a - Annéro Marinda Sakonaka Sakonaka			
Casing Dat	a:		42° 487.47 FQL 1.6039(18°, 4,78) 41 4994 4994 1996	999 - Berland Br. 198 (1999 - Caraona Lange						
Surfacejoints ofinch# Grade										
(Approved) (Rejected)										
Cementing Program										
Size of hole 7% Size of Casing 4½ Sacks cement required 250										
Type of Shoe used Flock Float collar used — Btm 3 jts welded Yes										
TD of hole 805 Set 807 Feet of 41/2 Inch 11 # Grade J-55										
New-used csg. @ 805 with 250 sacks neat cement around shoe										
+additives Plug down @ <u>/2:50 (</u> AM) (PM) Date <u>3/3//79</u>										
Cemert circulated No. of Sacks										
Cemerted by Denton Witnessed by MW										
Temp. Survey ran @ (AM) (PM) Date top cement @										
Casirg test @(AM) (PM) Date										
Nethcd Used Witnessed by										
		f @ (AM		1						
Nethod used Remarks: Toce 160' - Wtre 400' wesh out e 160'										
Remarks: Toce 160' - Wtre 400' wesh out e 160'										
· · · · · · · · · · · · · · · · · · ·			natu nda ng infanén dini infanén di ké " yang n	and a start speed on a start and a start of the start of		9999 (1999) (199				