## NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS									
Operator 2	Enterpre	Lease buly Finn				Well # 3			
ocation of Well	Unit 3305 330e	Section 22		Townsh		Range ZS	County Edd	County Eddy	
Drilling Contractor	s É	Type of Equipment Fotary to start 10-10-79							
APPROVED CASING PROGRAM									
Size of Ho	le Size	of Casing	-	Weight Per Foot		v or Used	Depth	Sacks Cemen	
7784	5	1/2'		f			800	250	cire,
		٣٠٠٠٣١ / ٢٠٠٠٩ / ٢٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠٠		n pitmen, si an emilian come e mu			لا تاريخ خطر بلغاني و روي و روي و روي		_,
Casing Data:									
Surfacejoints ofinch# Grade (Approved) (Rejected)									
Inspected by date									
Cementing Program									
Size of hole 71% Size of Casing 51/2 Sacks cement required									
Type of Shoe used $848$ Float collar used $\frac{F_{loat}}{B}$ Btm 3 jts welded $\frac{Yes}{Ves}$									
TD of hole <u>848</u> Set <u>850</u> Feet of 5½ Inch 14 # Grade <u>J-40</u> New-used csg. @ <u>850</u> with 150 sacks neat cement around shoe									
+saxadditives_2%CC									
Plug down @ //30 (##) (PM) Date 10-13-74									
Cement circulated No. of Sacks									
Cemented by Hewco Witnessed by BWWeaver									
Temp. Survey ran @ <u>8:00</u> (AM) ( <b>XM</b> ) Date <u>10-14-74</u> top cement @ <u>125</u>									
Casing test @(AM) (PM) Date									
Witnessed by									
Checked for shut off @ (AM) (PM) Date									
Method usedWitnessed by									
Nethod used Witnessed by Remarks: <u>4 Centerligens on Bottom 4 Joints</u>									
0									
Ready-mixed well to service 4 yels Miss.									
Λ		\	11					:	