

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Armstrong KS station.</i>		Well # <i>1</i>	
Location of Well	Unit <i>F 1980s 5600</i>	Section <i>16</i>	Township <i>17</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary & start approx. 3-2-79</i>		

APPROVED CASING PROGRAM

* *witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>400</i>	<i>circ.</i>
* <i>12 1/4"</i>	<i>8 7/8"</i>	<i>24</i>		<i>1400</i>	<i>circ.</i>
<i>7 7/8"</i>	<i>4 1/2 or 5 1/2"</i>			<i>8900</i>	<i>250</i>

Casing Data:

Surface _____ joints of _____ inch # Grade _____

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *insert* Btm 3 jts welded *yes*

TD of hole *1420'* Set *1420'* Feet of *8 5/8* Inch *24* # Grade *J-55*

New-used csg. @ *1420'* with *200 270 cc* sacks neat cement around shoe

+ *700* sax *Hall's Dite* additives *10# gilsonite - 1/4# floeak - 370 cc*

Plug down @ *11:45* (AM) (PM) Date *3/9/79*

Cement circulated *yes* No. of Sacks *60*

Cemented by *Halliburton* Witnessed by *Mrs. Stubbfield*

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks:

Inspected @ 1218'-934'

centerline @ 1218'-934'-1379'

last hole @ 1278'