

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instructi
verse side)CATE*
on reForm approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 9193

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Walnut Draw KV Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 7-16S-24E

Unit L NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FSL and 660' FWL of Section 7-16S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3724' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Set Prod. Casing & PB ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD7050' - Verbal approval was given by Mr. Jim Knauf w/ the USGS to Plug Back well as follows: 6435-6273' w/50 sacks of Class C and 5253-5076' w/65 sacks of Class C cement. WOC. - Ran 124 joints of 4½" 10.50# K-55 (5076') of casing set at 5076'. 1-Guide shoe at 5076', Diff-fill collar at 5035' and 8 centralizers. Cemented w/250 gallons mud flush, 25 9.4# pg, 200 sacks Howco-Lite w/3#/sack KCL, 5/10% CFR-2 followed w/200 sacks of Class C 3#/sack KCL, 5/10% CFR-2. PD 3:30 PM 4-22-79. Tested to 1500#. OK. WOC and ran Temperature Survey and found top of cement at 3340'; WLPBTD 5032'.

RECEIVED

MAY 10 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geol. Secty.

DATE

5-9-79

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

DATE

MAY 10 1979

CONDITIONS OF APPROVAL, IF ANY: