

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instructi
verse side)

DATE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-060894

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Exxon KU Fed. Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit F NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to different reservoirs.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

JUN 5 1979

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

O. C. C.

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2030' FNL & 1980' FWL of Section 31-17S-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3312' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Set Prod. Csg. ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9250' - Ran 4½" 11.6# and 10.5# casing as follows: 400' 11.6# N-80. 2200' 11.6# K-55, 4659' 10.5# K-55. 1900' 11.6# K-55 (Total 9159') of casing set at 9159'. 1-Guide shoe 9160', Diff float at 9118' and 10 centralizers. Cemented w/250 gallons mud flush wt. 9.3 w/KCL, 350 sacks Halliburton Lite 5/10% CFR-2, 2/10% Halad-22, 5#/sack KCL, tailed in w/120 sacks Class H 5/10% CFR-2, 2/10% Halad-22, 5#/sack KCL. PD 3:30 AM 5-10-79. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 7100'.

RECEIVED

MAY 29 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Johnson

TITLE

Geol. Secty

DATE 5-28-79

(This space for Federal or State office use)

APPROVED BY

Joe I. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 4 - 1979

CONDITIONS OF APPROVAL, IF ANY: