

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 18 1979

O. C. C.  
ARTESIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Summit Energy, Inc.	8. Farm or Lease Name Thigpen Et. Al.
3. Address of Operator 112 N. First St., Artesia, New Mexico 88210	9. Well No. 1Y
4. Location of Well UNIT LETTER F, 1800 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 16S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3526.8 GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Conductor Casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran and set 334' of 13 3/8" 48# casing. Used 300 sx Class C neat cement. Cement did not circulate. Used 1" pipe and found top of cement behind 13 3/8" casing at 84'. Cemented down 1" from 84' back to 62' with 50 sx cement. Cemented down 1" with 50 sx from 62' back to 40'. Filled hole with 8 yds. of redi-mix to surface. Completed at 7:00 p.m. (6-13-79).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gussitt TITLE Vice President-Production DATE 6/15/79

APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE JUN 19 1979

CONDITIONS OF APPROVAL, IF ANY: