

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYXEROX COPY  
SUBMIT IN TRIP DATE\*  
(Other Instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-025527-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Maralo Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Logon Draw  
New Los11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 22, T17S, R27E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1.

OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Mesa Petroleum Co.

3. ADDRESS OF OPERATOR

1000 Vaughn Building/Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)  
At surface

1980' FSL &amp; 660 FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3497.6 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Spudded - 13-3/8" casing XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well at 7:45 am on 7-18-79 with 17-1/2" hole. Ran 9 jts 13-3/8" casing, 54.5# K-55 ST&C (358.33) set at 355' RKB, insert float at 319', cement basket at 115' and 75'. Installed centralizer at 338', 315', 115', and 75'. Cemented with 75 sacks RFC + 5# kolite + 1/4# celloflakes followed by 375 sacks Class "C" + 2% cc + 1/4# celloflakes. PD at 3:15 am 7-19-79. Circulated 40 sacks to pit. Float did not hold. WOC total of 26-1/4 hours. Tested BOP's and casing on 7-20-79 to 600 psi - ok. Reduced hole to 12-1/4" and drilled ahead.

RECEIVED

JUL 23 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. MATHIS

TITLE Regulatory Coordinator

DATE July 20, 1979

(This space for Federal or State office use)

APPROVED BY

George H. Stewart

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 23 1979

\*See Instructions on Reverse Side

XC: MEC, TLS, JWH, JBH, JWJ, FILE, USGS