

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLA (E)  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0560378

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

O'Neill

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

West Henshaw (L. Henshaw)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 15, T-16S, R-30E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 128 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3811.0 G.L.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well at 5:30 P.M., August 18, 1979.

Ran 8-5/8" OD 20# casing and set at 466' KB

8-5/8" was cemented with 250 sacks of cement. (Circulated)

After standing cemented 9 hours compressive strength was 800#. Pressure tested to 1000#. Tested OK.

Drilled out cement after standing 18 hours.

Ran 4-1/2" OD 9.5# casing to 2600' KB and cemented with 400 sacks of cement.

Perforated: 2504'-2517' (2) shots per foot.

Fraced from 2504'-2517' with 40,000 gallons gelled water and 40,000# 20/40 mesh bulk sand.

RECEIVED

OCT 18 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Lowell Hawkins*

TITLE

Assistant

Field Superintendent

DATE October 17, 1979

(This space for Federal or State office use)

APPROVED BY *GEORGE H. STEWART*

TITLE ACTING DISTRICT ENGINEER

DATE OCT 17 1979

CONDITIONS OF APPROVAL, IF ANY: