

Form 9-331
May 1965UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
GCS-510)Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

NM 025527

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back a well. For such proposals, use "APPLICATION FOR PERMIT" for such proposals.

RECEIVED

1. WELL TYPE: GAS WELL ☒ OTHER ☐

NOV 7 1979

2. NAME OF OPERATOR

Mesa Petroleum Co

3. ADDRESS OF OPERATOR

1000 Vaughn Building / Midland, Texas 79701

O. C. C.
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See instructions on page 11 below.)
At location:

2130' FNL & 1650' FEL

5. ELEVATION

6. ELEVATIONS (Show whether DE, RL, OR, etc.)

3423.7' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Willis Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILLCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28, T17S, R27E

12. COUNTY OR PARISH, 13. STATE

Eddy

N. Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

1. STOP WATER SHUT-OFF	2. TEST OR ALTER CASING
3. FRACTURE TREATMENT	4. MULTIPLE COMPLETION
5. FLOOD OR ACIDIZE	6. ABANDON*
7. PLUG WELL	8. CHANGE PLANS
9. OTHER	

SUBSEQUENT REPORT OF:

1. WATER SHUT-OFF	2. REPAIRING WELL
3. FRACTURE TREATMENT	4. ALTERING CASING
5. SHOOTING OR ACIDIZING	6. ABANDONMENT*
7. (Other) Spudding & 13-3/8" casing	8. ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

12. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See instructions on page 11 below.)
If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded well with 17-1/2" hole on 10-31-79. Drilled to 350' on 10-31-79. Ran 9 jts 13-3/8", 48#, H40, STC casing set at 350' with guide shoe on bottom, insert float at 307.69' and centralizers at 320' and 290' for a total length of 356'. Cemented with 275 sx class "C" + 2% CaCl + 1/4# celloflakes followed with 100 sx class "C" + 2% CaCl. Circulated 50 sx of good cement. PD at 10:30 PM 10-31-79. Cement did not fall back. WOC at 13-1/2 hrs. Tested casing to 1500 psi for 30 min - ck. Reduced hole to 11" and drilled ahead on 11-1-79.

NOV 5 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

15. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Regulatory Coordinator

DATE

November 2, 1979

(This space for signature of person making report.)
GEORGE H. STONE

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

XC: TIS, JWH, FILE, MLC, USGS, WI OWNERS 11-2-79 V.H.