INSTRUCTIONS

This form is to be filed with the appropriate clastrict Office of the Commission not later than 26 – 23 after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be necessared depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30, through 34 shall be reported for each zone. The form is to be filed in quintuplicate exception state 1 md, where six copies are reguired. Coe Bule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

.

	Sout	heastern New Mexico	Northwe	stem New Mexico
т.	Anhy	T. Canyon	T Ojo Alamo	T. Penn. ''B''
т.	Salt	T. Strawn	_ T. Kirtland-Fruitland	T. Penn. "C"
в.	Salt	T. Atoka	T. Fictured Cliffs	T. Penn. "D"
Т.	Yates	T. Miss	T. Cliff House	T. Leadville
т.	7 Rivers732 *	T_ Devonian	T. Menefee	T. Madison
т.	Queen	T. Silurian	T. Point Lookout	T. Elbert
Т.	Grayburg	T. Montoya	T. Mancos	T. McCracken
τ.	San Andres	T. Simpson	_ T. Gallup	T. Ignacio Qtzte
				T. Granite
				T
Т.	Tubb	T. Granite	T. Todilto	T
				T
				T
				T
				T
Т	Cisco (Bough C)	T	T. Penn. ''A''	T
		OIL OR GA	S SANDS OR ZONES	
No.	1, from		. No. 4, from	to
No.	2, from	to	No. 5, from	
No.	3, from	to	No. 6, from	to
		IMPORTA	NT WATER SANDS	

Include data on rate of water inflow and elevation to which water rose in hole.								
No. 1, from	to	et						
No. 2, from	to	ct						
No. 3, Irom	to	ct						

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation		From	T۰	Thickness 'in Feet	Formation
0	10	10	Top soil.					
10	60	50	Redbed					
60	70	10	Gravel					·
70	90	20	Redbed					
90	120	30	Limestone					
120	250	130	Limestone w/layer	s of rec	lbed			
250	470	220	Redbed					
470	590	120	Limestone					
590	800	210	Limestone w/layer	s of red	lbed			
						ļ		
						1		