

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>allen Ganett</i>		Lease <i>Leon State</i>		Well # <i>1</i>	
Location of Well	Unit <i>660N 660E</i>	Section <i>32</i>	Township <i>16</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>yucca Drilling Co.</i>		Type of Equipment <i>Rotary to start approx. 10-20-79</i>			
* <i>witness</i> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>10"</i>	<i>7"</i>	<i>20"</i>		<i>1085</i>	<i>350 circ.</i>
<i>6 3/4"</i>	<i>5 1/2"</i>	<i>14</i>		<i>2200</i>	<i>150</i>
Casing Data:					
Surface _____ joints of _____ inch <i>7</i> # Grade <i>J-55</i>					
(Approved) (Rejected) _____					
Inspected by <i>M.S.</i> date <i>12/21/79</i>					
Cementing Program					
Size of hole <i>9 7/8"</i> Size of Casing <i>7"</i> Sacks cement required _____					
Type of Shoe used <i>guide</i> Float collar used <i>insert</i> Btm 3 jts welded <i>yes</i>					
TD of hole <i>1150'</i> Set <i>1150'</i> Feet of <i>7"</i> Inch <i>23</i> # Grade <i>J-55</i>					
New-used csg. @ <i>1150'</i> with <i>180</i> sacks neat cement around shoe					
+ <i>200</i> sax <i>Hall, lite</i> additives <i>None</i>					
Plug down @ <i>3230</i> (AM) (PM) Date <i>12/22/79</i>					
Cement circulated <i>yes</i> No. of Sacks <i>100</i>					
Cemented by <i>Halliburton</i> Witnessed by <i>Mike Stuberfeld</i>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

<i>centralizers @ 1110'-1080'</i> <i>lost hole break @ 1030'</i>					